


LP400

Direct Thermal Printer



- ◆ 152mm per second high printing speed
- ◆ Open access for easy media loading
- ◆ Auto-calibration of media
- ◆ Head-up sensor and platen replacement
- ◆ Free bundled labeling software and windows drivers



SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390

Site: www.xl-scan.com

E-mail: sales@xl-scan.com



LP400 Direct Thermal Printer



Printing Features

Resolution	203 DPI
Print method	Direct Thermal
Print speed	152mm(6")/s
Max.print width	108 mm (4.25")
Max.print length	1778 mm (70")

Media

Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20 ~ 118 mm (0.78 " ~ 4.6 ")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Media core diameter	25.4 ~ 76.2 mm (1 " ~ 3 ")
Label length	10~1778 mm (0.39"~70")

Performance Features

Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	USB / USB+Serial / USB+Serial+Lan Optional:Bluetooth or Wifi
Sensors	1.Gap sensor 2.Cover opening sensor 3.Black mark sensor

Fonts/Graphics/Symbologies

Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, 8, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits, add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0° 、 90° 、 180° 、 270°
Emulaion	TSPL 、 EPL 、 ZPL 、 DPL

Physical Features

Dimension	240(D) x 212(W) x172(H) mm
Weight	2.15kg

Reliability

Warranty	One year for the printer
Print head	30 km or first arrival first

Software

Driver	Windows/ Linux/ Mac
SDK	Windows/ iOS / Android

Power supply

Input	AC 100-240V, 1A, 50-60Hz
Output	DC 24V, 2.5A, 60W

Options

Factory Options	1.Peeling machine 2. Bluetooth 3. WIFI 4.Serial
Dealer Options	1.External paper roll holder and 1 "paper roll 2.Extension board for external paper roll holder 3.Shipment waybill box

Environmental Conditions

Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40-140°F), Humidity:10 ~ 90% non-condensing

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390

Site: www.xl-scan.com

E-mail: sales@xl-scan.com

