

RP8060P

Mobile Label Printer



- ◆ Support direct USB charging;
- ◆ Long lasting battery life;
- ◆ Dual mode bluetooth;
- ◆ OLEO screen available;
- ◆ TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.



RP8060P



Mobile Label Printer

Printing	
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	Max. 70mm (2. 7") / s
Max.print width	72 mm (2.8")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	20 mm~76 mm
Media thickness	0.06 mm~0.254 mm
Label roll diameter	50mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	USB+Bluetooth / USB+WIFI
Screen	OLED (1.3") Resolution:128*64 pix
Sensors	1.Gap sensor 2.Cover opening sensor 3.Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code.Aztec
Rotation	0° 、 90° 、 180° 、 270°
Emulaion	TSPL、EPL、ZPL、DPL、CPCL、ESC/POS
Physical Features	
Dimension	124x108x61mm (DxWxH)
Weight	357 g
Reliability	
Printer head life	30Km
Software	
Operation system	Windows/ Android/ iOS
SDK	Windows/ Android/ iOS
Power supply	
Output	DC 9V/1A
Battery	7.4 V/2600mAh
Environmental Conditions	
Operation environment	5~40°C (41~104°F) , Humidity: 25~85% no condensing
Storage environment	-40~60°C (-40~140°F) , Humidity: 10~90% no condensing



SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390

Site: www.xl-scan.com

E-mail: sales@xl-scan.com

